The state of the s

UTILITY PATENT APPLICATION TRANSMITTAL (Large Entity)

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Docket No. P-5015

Total Pages in this Submission 33

TO THE ASSISTANT COMMISSIONER FOR PATENTS

Box Patent Application Washington, D.C. 20231

Transmitted herewith for filing under 35 U.S.C.	111(a) and 37 C.F.R.	1.53(b) is a new utility	patent application for ar
invention entitled:			

	mitted ion er			filing under 35	U.S.	.C. 111(a) and 3	37 C.F.R. 1.53(b) is a new utility patent ap	pplication for an
								TION FOR OPTICAL EXA	MINATION 23 65.0
and in	vente	d by:							
BR	IAN C	G. SCI	RIVENS	, DWIGHT LI	VINC	GSTON, ROBEI	RT S. FRANK a	nd KLAUS W. BERNDT	ρ 8 9 9 9
lf a C	ONT	NUA	TION AI	PPLICATION,	chec	ck appropriate b	ox and supply	the requisite information:	
	Conti	nuati	on 🗆	Divisional		Continuation	-in-part (CIP)	of prior application No.:	
Whic	h is a								
	Conti	nuati	on 🗆	Divisional		Continuation	-in-part (CIP)	of prior application No.:	
Whic	h is a	•							
	Conti	nuati	on 🗆	Divisional		Continuation	-in-part (CIP)	of prior application No.:	
-									
Encid	osed a	are:				Application	on Elements		
4	15.01	F11:	,		.1 1				
1.	X	Filin	g tee as	calculated an	d trar	nsmitted as des	cribed below		
2.	X	Spe	cification	n having		13	pages and ir	ncluding the following:	
	a.	X	Descrip	otive Title of th	e Inv	ention			
	b.		•			ted Applications	s (if applicable)		
								velopment (if applicable)	
	d.					ppendix (if appl			
	e.	_		ound of the In			, od 2, o		
	f.	X		ummary of the					
	g.				ne Dra	awings <i>(if drawi</i>	ings tiled)		
	h.	×	Detaile	d Description					
	i.	X	Claim(s	s) as Classified	d Belo	OW			
	j.	\boxtimes	Abstrac	ct of the Disclo	sure				

UTILITY PATENT APPLICATION TRANSMITTAL (Large Entity)

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Docket No. P-5015

Total Pages in this Submission 33

Application Elements (Continued) ☑ Drawing(s) (when necessary as prescribed by 35 USC 113) a. 🗌 Formal Number of Sheets b. X Informal Number of Sheets 5 ☑ Oath or Declaration Newly executed (original or copy) Unexecuted a. 🔀 b. Copy from a prior application (37 CFR 1.63(d)) (for continuation/divisional application only) c. 🗵 With Power of Attorney ■ Without Power of Attorney DELETION OF INVENTOR(S) d. 🔲 Signed statement attached deleting inventor(s) named in the prior application, see 37 C.F.R. 1.63(d)(2) and 1.33(b). ☐ Incorporation By Reference (usable if Box 4b is checked) The entire disclosure of the prior application, from which a copy of the oath or declaration is supplied under Box 4b, is considered as being part of the disclosure of the accompanying application and is hereby incorporated by reference therein. ☐ Computer Program in Microfiche (Appendix) Nucleotide and/or Amino Acid Sequence Submission (if applicable, all must be included) a. Paper Copy b. Computer Readable Copy (identical to computer copy) c. Statement Verifying Identical Paper and Computer Readable Copy **Accompanying Application Parts** Assignment Papers (cover sheet & document(s)) ☐ 37 CFR 3.73(B) Statement (when there is an assignee) 11. Information Disclosure Statement/PTO-1449 Copies of IDS Citations ☐ Preliminary Amendment 13. Acknowledgment postcard 14. Certificate of Mailing

First Class

UTILITY PATENT APPLICATION TRANSMITTAL (Large Entity)

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Docket No. P-5015

Total Pages in this Submission 33

							<u> </u>	
	-		A	ccompanying Ap	plication Pa	arts (Co	ontinued)	
15.		Certified Co	ppy of Priority	Document(s) (if fo	reign priorit	y is clain	ned)	
16.		Additional E	Enclosures (p	lease identify below	N):		NATIONAL AND ADDRESS OF THE PARTY OF THE PAR	
							4 - 1974 4 - 1974 Add Add Add Add Add Add Add Add Add Ad	
				Fee Calcula	tion and Tr	ansmitt	al	
divisions or or or or or or or or				CLAIMS A	S FILED			e de la dichie de la della
The state of the s	For		#Filed	#Allowed	#Extra		Rate	Fee
Total	Claim	s	18	- 20 =	0	х	\$18.00	\$0.00
Indep	. Clair	ns	1	- 3 =	0	х	\$78.00	\$0.00
Multi	ple De	pendent Cl	aims (check	if applicable)]			\$0.00
7							BASIC FEE	\$690.00
OTH	IER FE	E (specify	purpose)					\$0.00
The second secon							TOTAL FILING FEE	\$690.00
	\ checl	k in the amo	ount of	to c	over the filin	g fee is	enclosed.	
				thorized to charge		_		
a				e copy of this sheet				
	X	_	amount of		s filing fee.			
	X	-	overpaymen		indos 27 O F	ED 440	6 and 1 17	
				iling fees required u			e Notice of Allowance,	
	_		37 C.F.R. 1		at the maili	19-01-1116	Notice of Allowance,	
				V = 1.	(<u> </u>	1	4(·)e).6 ==	
					⟨ _R	ruce S. V) Signature Weintraub, Esq. / Reg. No. 3	4.277
Dated	l: Se _I	otember 27,	2000				ickinson and Company	,//
					1	Becton I	Drive	
							Lakes, New Jersey 07417 01-847-7096	
							01-04/-/090 -8 <i>47-5377</i>	

CC:

METHOD FOR OBTAINING INCREASED PARTICLE CONCENTRATION FOR OPTICAL EXAMINATION

5

10

FIELD OF THE INVENTION

The present invention relates to a method and apparatus for analyzing a blood or other biological fluid sample in a quiescent state, whereby particulate constituents of biological samples that contain sparse populations of cellular species of interest can be enumerated and inspected using an optical scanning instrument. Specifically, this invention relates to a method and apparatus for obtaining an increased cellular or particulate concentration within the use of said optical scanning method.

15

BACKGROUND OF THE INVENTION

The formation of appropriate cellular or particulate layers for later optical examination is important to many fields. One of these fields is hematology, where several methods and devices have been described for obtaining clinically useful cell concentrations.

20

25

A method and apparatus for analyzing a blood or other biologic fluid sample in a quiescent state without the need for separate fluid streams passing through the blood sample during the analysis is described in U.S. Serial Nos. 09/248,135 and 09/249,721. Although this method simplifies the analysis procedure and yields the full compliment of CBC parameters it also possesses several disadvantages. One disadvantage of the apparatus is that the concentration of cells in the examination

layer is not controlled. This can lead to difficulties in optically examining cell volume and morphology. Another disadvantage of the aforementioned apparatus is that the field of cells may be too sparse in clinically relevant samples to complete scanning in a timely manner.

5

10

15

20

25

- U.S. Patent Nos. 5,627,041 and 5,912,134 describe an apparatus and method for cytometric measurement of cell populations using fluorescent markers. However, a disadvantage of this method is that, if the sample under test is blood, it requires addition of diluent in such quantities that white blood cells (WBCs) with depressed counts are not very numerous in the sample and may require extremely long examination times to locate them. Moreover, if the cell counts within the undiluted blood are low, clinically relevant cell populations present in the sample may not be detected in the diluted sample. For example, patients who undergo chemotherapy regimens may have depressed white cell counts in the range of 1000 cells/ μ L and less. Cytometric examinations are typically searching for a sub-population of these cells, further reducing the likelihood of locating them.
- U.S. Patent No. 4,790,640 discloses a wedge shaped device for trapping rigid particles, such as sickle cells in blood. However, a disadvantage of the device is that the selection of cell sizes is accomplished by thickness of the chamber alone, which can exhibit substantial manufacturing variation over the examination area, causing a corresponding loss of ability to separate by size.

Consequently, it would be desirable to have a method and apparatus for obtaining the desired cellular concentration in a blood or other biologic sample which can mitigate the effect of a separate dilution step and addition of diluting fluids.

10

15

20

25

SUMMARY OF THE INVENTION

It is an objective of the present invention to provide channels in a separation wall inside a separation chamber, said channels having appropriate size and dimensions to allow at least one undesired particle species to pass while excluding larger particles from passing through, thereby arriving at a predetermined increased volume fraction of the desired particles.

It is another objective of the present invention to incorporate at least two separating channels in a separation wall in a separation chamber, the channels having channel sizes selected to allow at least one cell species and the substantially liquid component of the sample to pass through them, arriving at a desired concentration of larger cell types in the first compartment in front of the separation wall. A further embodiment of the present invention is to have a plurality of separating channels in the separating wall having one channel size selected to allow at least one cell species and the substantially liquid component of the sample to pass through them.

It is a further objective of the present invention to regulate the volume fraction of cellular or particle components of a specimen by means of an array of separating channels which effect their selection by means of size exclusion during flow between two adjoining compartments.

It is another objective of the present invention to increase the concentration of larger particles for cytometric examination of sparse populations by allowing only smaller particles and substantially liquid components to pass through the channels into a subsequent chamber.

It is a still further objective of the present invention to create an accurate spacing between two opposing containment walls to allow for the optimal formation of desired regions where all particles of interest lie in the same focal plane, allowing an accurate determination of the chamber thickness without relying on extraneous equipment and manipulations for height calibration.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is an isometric view of the particle separation chamber with the lid removed showing the separation channels and adjacent cell examination areas.

10

25

5

- FIG. 2 is an isometric view of the bottom portion of the separation chamber showing the disposition of the separation channels.
- FIG. 3 shows a detailed view of another embodiment of the separation channels.
 - FIG. 4 shows an isometric view of another embodiment of the separation channels.
- 20 FIG. 5 is a schematic view of a particle separation chamber with increased analytical sensitivity.

DETAILED DESCRIPTION OF THE INVENTION

The present invention relates to a method and apparatus for obtaining an increased cellular or particulate concentration in a substantially dilute sample. The apparatus includes a sample chamber which has opposing sample containment

walls, at least one of which is transparent. The sample chamber is separated into adjoining compartments which are in fluid communication by means of a multiplicity of channels aligned substantially parallel to each other and which traverse a separating wall between the two compartments. Filling of the chamber results in a substantially quiescent sample ready for further examination.

In a preferred embodiment, a chamber is used to manipulate blood components and one type of channel in the array is of sufficient size and dimensions to allow red blood cells (RBCs) to pass while excluding larger white blood cells (WBCs). The dimensions of the channel to create the desired size exclusion are nominally, in a preferred embodiment, 3 to 10 μ m deep x 5 to 50 μ m wide. Dimensions within this range have been selected to effect the desired volume flow rate of RBCs, or particle-containing sample. In a modification of the invention, another type of channel in the array is of sufficient size and dimensions to exclude RBCs and WBCs from passing while allowing the liquid component of the specimen to pass freely. The dimensions of the channel to create the desired size exclusion are nominally, in a preferred embodiment, 0.5 to 1.5 μ m deep x 50 to 1000 μ m wide. Dimensions within this range are selected to effect the desired volume flow rate of the liquid-only portion of the sample.

As the blood sample or particle containing specimen flows from the first compartment and through the array of channels into the subsequent compartment, the relative volume fraction of WBCs, RBCs, or other particles is increased in the first compartment. The two streams, one containing substantially undiluted blood or particles, and the other, a liquid-only fraction, recombine in the subsequent compartment to form a liquid sample having a reduced volume fraction of cells or particles in the subsequent compartment. A further benefit of the invention is to

provide a thickness within the chamber during manufacture, which is more accurate than would otherwise be obtained since the wall surrounding the interior of the chamber acts to hold the two opposing sample containment walls, that function as optical windows apart at a fixed and accurate distance.

5

Figure 1 is merely exemplary and is not intended to limit the present invention in any way. A separation chamber in accordance with the present invention can have notches in one or more compartments of the separation chamber, or no notches at all.

10

15

20

25

In the embodiment of the present invention demonstrated in Figure 1, the separation chamber is surrounded by a wall (1) which is used to carry an optically transparent lid (not shown) allowing for optical observation and to contain the liquid sample. The separation chamber is divided into two compartments by a separation wall (2) which has separation channels on top of it. Details of different embodiments for separation wall (2) are shown in Figures 2, 3, and 4. Returning to Figure 1, fluid fills the first compartment through a sample entrance (3), which is surrounded by an extension (11) of wall (1), and moves into the first compartment (4) of the chamber. Upon proceeding, the liquid encounters a first notch (5) displaced laterally across the flow path. The notch creates a momentary barrier to progression of the advancing fluid meniscus until the meniscus has contacted the notch across the whole width of the chamber. Eventually the fluid wets into the notch, allowing the fluid to advance to the next notch (6) where the meniscus is again evened out. The fluid advance continues in this manner until it reaches the separation wall (2). The fluid continues to advance through the separation wall and separation channels to the second compartment (7) until finally stopping at its far end (8). Adequate venting of air while the chamber fills with liquid is provided by a series of venting-channels (13) on top of

10

15

20

25

wall (1). To allow for a free passage of air out of channels (13), walls (1) and (11) are surrounded by a moat (12). During the filling process, the particles of interest, are prevented from passing through the separation channels that traverse separation wall (2), and as a consequence, concentrate in the first compartment (4). After the fluid fills the subsequent first and the second compartment it becomes quiescent, allowing optical examination.

Figure 2 shows a separation wall having two different channels of different sizes (9) and (10). The channel labeled (9) is sized to allow only particles smaller than a certain size to pass and the channel labeled (10) is sized to allow only liquid to pass. It has been found through experimentation that these channels can be sized appropriately to exclude cell or particle sizes of interest.

Figure 3 shows a separation wall (16) with a plurality of one type of separating channel (17) disposed laterally across its full width.

Figure 4 shows another embodiment of the separating channels, with a plurality of a first channel (14) which allows cellular or particulate species to pass through it, while allowing a liquid portion devoid of this species to pass through a plurality of a second channel (15) disposed in an array alongside the first channel (14).

In another embodiment of the present invention, which is depicted in Figure 5, increased analytical sensitivity can be attained by enlarging the volume of the second compartment, allowing the sample portion in the first compartment to accumulate larger cells over an increased volume.

10

15

20

25

In the embodiment of Figure 5, the separation chamber is surrounded by a wall (21) which is again used to carry an optically transparent lid (not shown) allowing for optical observation and to contain the liquid sample. The separation chamber is divided into two compartments (22) and (23) by a separation wall (24) which has the separation channels on top of it. Separation wall (24) is U-shaped in order to make it as long as possible. In operation, fluid fills the first compartment (22) through a sample entrance (25), which is surrounded by an extension (27) of wall (21), and moves into the first compartment (22) of the chamber. Upon proceeding, the liquid encounters a first notch (25) displaced laterally across the flow path. The notch creates a momentary barrier to progression of the advancing fluid meniscus until the meniscus has contacted the notch across the whole width of the chamber. Eventually the fluid wets into the notch, allowing the fluid to advance to the next notch (26) where the meniscus is again evened out. The fluid advance continues in this manner until it reaches separation wall (24). The fluid continues to advance through separation wall (24) and the separation channels to the second compartment (23) which is surrounded by wall extension (28). Wall (21) and wall extension (28) are equipped with air-venting channels (29) and (30), respectively. To allow for a free passage of air out of channels (29) and (30), walls (21), (27), and (28) are surrounded by a moat (31) in base plate (32). The lid is resting on walls (21), (27), and (28).

During the filling process, the particles of interest are prevented from passing through the separation channels that traverse separation wall (24), and as a consequence, concentrate in the first compartment in a U-shaped area (33) in front of separation wall (24). As mentioned above, compartment (23) behind separation wall (24) has an increased volume, which, in connection with the elongated U-shaped separation wall (24) allows one to process a larger sample volume, as

compared to the embodiments shown in Figures 1, 2, 3, and 4. In other words, the embodiment of Figure 5 is suitable to achieve reasonable particle concentrations for analysis in front of separation wall (24), even if the particle concentration in the incoming sample is rather low.

What is claimed is:

- 1. A method for obtaining a liquid sample having an increased cellular or particulate concentration for optical examination comprising:
- 5 (a) providing an apparatus comprising:
 - a separation chamber;
 - a wall surrounding said separation chamber;
 - a sample entrance;
 - venting channels;
- a separation wall in said separation chamber dividing said chamber into two compartments, said separation wall having at least one separation channel; and a flow path in said separation chamber;
 - (b) depositing a liquid sample into the sample entrance of said apparatus;
 - (c) allowing the sample to flow into the separation chamber;
- (d) allowing the sample to flow along the flow path in said separation chamber;
 - (e) allowing the sample to advance to the separation wall;
 - (f) allowing the sample to advance through the separation wall and the at least one separation channel;
- 20 (g) allowing the sample to advance to the second compartment;
 - (h) allowing the sample to advance to the end of the separation chamber; and
 - (i) obtaining in the first compartment, the sample having an increased cellular or particulate concentration, which has been prevented from passing through said separation channel(s).
 - 2. The method according to Claim 1 wherein said liquid sample is blood.


- 3. The method according to Claim 1 wherein said apparatus further comprises a lid portion.
- 5 4. The method according to Claim 3 wherein said lid portion has at least one opening for sample delivery.
 - 5. The method according to Claim 1 wherein said separation wall has at least one first separation channel and at least one second separation channel.
 - 6. The method according to Claim 5 wherein said separation channels are of different sizes.
- 7. The method according to Claim 5 wherein said first separation channel is about 3 to 10 μ m deep by 5 to 50 μ m wide.
 - 8. The method according to Claim 5 wherein said second separation channel is about 0.5 to 1.5 μm deep by 50 to 1000 μm wide.
- 9. The method according to Claim 1 wherein said apparatus further comprises a plurality of notches in said separation chamber.
- 10. The method according to Claim 1 wherein said apparatus further comprises a plurality of notches in said first compartment of said separation chamber.


- 11. The method according to Claim 1 wherein said apparatus further comprises a plurality of notches in said second compartment of said separation chamber.
- The method according to Claim 1 wherein said apparatus further comprises a plurality of notches in said first compartment and second compartment of said separation chamber.
- 13. The method according to Claim 1 wherein said separation wall has a plurality of separation channels of the same size.
 - 14. The method according to Claim 1 wherein said separation wall has a plurality of separation channels of different sizes.
- 15. The method according to Claim 9, further comprising allowing the sample to flow past each notch in the separation chamber.
 - 16. The method according to Claim 10 further comprising, after step (d), allowing the sample to flow past each notch in the first compartment.
 - 17. The method according to Claim 11 further comprising, after step (g), allowing the sample to flow past each notch in the second compartment.
- 18. The method according to Claim 12 further comprising, after step (d), allowing the sample to flow past each notch in the first compartment; and after step (g), allowing the sample to flow past each notch in the second compartment.


ABSTRACT OF THE INVENTION


The present invention relates to a method and apparatus for analyzing a blood or other biological fluid sample in a quiescent state, whereby particulate constituents of biological samples that contain sparse populations of interesting cellular species can be enumerated and inspected using an optical scanning instrument. Specifically, this invention relates to a method and apparatus for obtaining increased cellular or particulate concentrations within the use of said optical scanning method.

10 #35971












Fig. 5

Docket No. P-5015

Declaration and Power of Attorney For Patent Application

English Language Declaration

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name,

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

	METHOD FOR OBTAINING EXAMINATION	INCREASED PARTI	CLE CONCE	NTRATION FOR OPT	ICAL	
	the specification of which					
	(check one)					
2 11 2 11 2 11	☑ is attached hereto.					
	☐ was filed on		as United S	States Application No	or PCT	International
	Application Number					
ri Mi	and was amended on					
	-		(if ap	plicable)		
	I hereby state that I have reincluding the claims, as ame	eviewed and under ended by any ame	stand the conduction	ontents of the above red to above.	identified	I specification,
	I acknowledge the duty to known to me to be mater Section 1.56.	disclose to the Unitial to patentability	ted States F as defined	Patent and Trademar in Title 37, Code o	k Office f Federa	all information I Regulations,
	I hereby claim foreign price Section 365(b) of any foreign any PCT International applicated below and have also inventor's certificate or PCT on which priority is claimed.	gn application(s) f cation which desigi identified below, by	or patent or nated at leas / checking th	inventor's certificate one country other to the box, any foreign a	e, or Sec than the polication	tion 365(a) of United States, n for patent or
	Prior Foreign Application(s)				Priority	Not Claimed
	(Number)	(Country)	(1	Day/Month/Year Filed)		
	(Number)	(Country)		Day/Month/Year Filed)		
	(Number)	(Country)		Day/Month/Year Filed)		
	` - ' /	((1	Jaynwonuii Lai Filed)		

Ų.
" "
Same
w.
The state of
E
E
THE PLAN THE TANK
Hall Hall

(Application Serial No.)	(Filing Date)	
(Application Serial No.)	(Filing Date)	_
(Application Serial No.)	(Filing Date)	_
insofar as the subject matter of ea United States or PCT International U.S.C. Section 112, I acknowledge Office all information known to me	ach of the claims of this ap application in the manner the duty to disclose to the to be material to patenta	g the United States, listed below and, oplication is not disclosed in the prior provided by the first paragraph of 35 to United States Patent and Trademark bility as defined in Title 37, C. F. R
insofar as the subject matter of ea United States or PCT International U.S.C. Section 112, I acknowledge Office all information known to me	ach of the claims of this application in the manner to the duty to disclose to the to be material to patentalle between the filing date of	g the United States, listed below and, oplication is not disclosed in the prior provided by the first paragraph of 35 to United States Patent and Trademark bility as defined in Title 37, C. F. R.,
insofar as the subject matter of ear United States or PCT International U.S.C. Section 112, I acknowledge Office all information known to me Section 1.56 which became availab or PCT International filing date of thi	ach of the claims of this application in the manner of the duty to disclose to the set to be material to patentalle between the filing date of application:	

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith. (list name and registration number)

Richard J. Rodrick, Reg. No. 26,985 John L. Voellmicke, Reg. No. 30,348 Allen W. Wark, Reg. No. 30,503 Robert M. Hallenbeck, Reg. No. 31,364 Nanette S. Thomas, Reg. No. 33,310 Bruce S. Weintraub, Reg. No. 34,277 Arthur D. Dawson, Reg. No. 35,113

David W. Highet, Reg. No. 30,265 Eric M. Lee, Reg. No. 30,471 Donna R. Fugit, Reg. No. 32,135 Alan W. Fiedler, Reg. No. 33,690 Susan A. Capello, Reg. No. 34,560 Richard E. Brown, Reg. No. 30,934 Kathleen Dal Bon, Reg. No. 29,829

Send Correspondence to: RICHARD J. RODRICK, ESQ.

BECTON, DICKINSON AND COMPANY

1 BECTON DRIVE

FRANKLIN LAKES, NEW JERSEY 07417-1880

Direct Telephone Calls to: (name and telephone number)

BRUCE S. WEINTRAUB, ESQ. / 201-847-7096

Full name of sole or first inventor BRIAN G. SCRIVENS	
Sole or first inventor's signature	Date 22-Sunt 00
Residence 1089 NESBITT ROAD, COLORA, MARYLAND 21917	300
Citizenship U.S.A.	
Post Office Address 1089 NESBITT ROAD, COLORA, MARYLAND 21917	

Full name of second inventor, if any DWIGHT LIVINGSTON	
Second inventor's signature Residence	Date 2 2 - SeV-ご
1908 ANGLESIDE ROAD, FALLSTON, MARYLAND 21047	
Citizenship U.S.A.	
Post Office Address 1908 ANGLESIDE ROAD, FALLSTON, MARYLAND 21047	

III
T.
State State
10,72
1000 P
H
7
la constitution

BERT S. FRANK	
I inventor's signature	Date Cy (ZC)
dence 2 BROKEN LUTE WAY, ELLICOTT CITY, MARYLAND 21042	
enship ${f A.}$	
Office Address 2 BROKEN LUTE WAY, ELLICOTT CITY, MARYLAND 21042	
name of fourth inventor, if any	
AUS W. BERNDT	
th inventor's signature - Klairs G. Bendf	9/22/00 Date
dence LOCHVIEW TERRACE, TIMONIUM, MARYLAND 21093	•
enship A.	
Office Address LOCHVIEW TERRACE, TIMONIUM, MARYLAND 21093	
name of fifth inventor, if any	
inventor's signature	Date
dence	
enship	
Office Address	
name of sixth inventor, if any	
inventor's signature	Date
dence	
enship	
Office Address	